

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

SYNONYMS

"Product Code: 200302", "Epoxy Part B hardener two component paint primer coating low temperature"

PROPER SHIPPING NAME

PAINT

PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Part B or Hardener of a 2 pack epoxy coating system. Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Apply by brush, hand roller or spray atomisation. after viscosity reduction with thinner. Part B hardener specifically used for curing at low temperatures.

SUPPLIER

Company: Wattyl Pty Ltd

Address:

4 Steel St

Blacktown

NSW, 2148

AUS

Telephone: +61 2 9621 6255

Emergency Tel: 1800 039 008

Fax: +61 2 9831 4244

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

S5

RISK

Risk Codes	Risk Phrases
R10	Flammable.
R20/21/22	Harmful by inhalation in contact with skin and if swallowed.
R36/37/38	Irritating to eyes respiratory system and skin.
R40(3)	Limited evidence of a carcinogenic effect.
R43	May cause SENSITISATION by skin contact.
R52	Harmful to aquatic organisms.
R65	HARMFUL- May cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes	Safety Phrases
S23	Do not breathe gas/fumes/vapour/spray.
S51	Use only in well ventilated areas.
S09	Keep container in a well ventilated place.
S53	Avoid exposure - obtain special instructions before use.
S401	To clean the floor and all objects contaminated by this material use water and detergent.
S07	Keep container tightly closed.
S13	Keep away from food drink and animal feeding stuffs.
S27	Take off immediately all contaminated clothing.
S26	In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	This material and its container must be disposed of as

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 2 of 8

Section 2 - HAZARDS IDENTIFICATION

hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
xylene	1330-20-7	10-30
n- butanol	71-36-3	10-30
polyamine adduct		10-30
2, 4, 6- tris[(dimethylamino)methyl]phenol	90-72-2	1-5
benzyl alcohol	100-51-6	1-5

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

To treat poisoning by the higher aliphatic alcohols:

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.

For acute or short term repeated exposures to xylene:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- Pulmonary absorption is rapid with about 60-65% retained at rest.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
 - May be violently or explosively reactive.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

- Moderate fire hazard when exposed to heat or flame.
- Combustion products include: carbon dioxide (CO₂), carbon monoxide (CO), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.

HAZCHEM: 3[Y]

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
 - Clean up all spills immediately.
- Slippery when spilt.

MAJOR SPILLS

Chemical Class: aromatic hydrocarbons

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
--------------	------	-------------	------------	-------------

- Slippery when spilt.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
 - Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
 - Ensure electrical continuity by bonding and grounding (earthing) all equipment.
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of overexposure occurs.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C).

STORAGE INCOMPATIBILITY

Avoid storage with strong acids, acid chlorides, acid anhydrides, oxidising agents.

Avoid strong acids.

- Avoid contact with copper, aluminium and their alloys.

Incompatible with aluminium. DO NOT heat above 49 deg.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 4 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³
Australia Exposure Standards	xylene (Xylene (o- , m- , p- isomers))	80	350	150	655		
Australia Exposure Standards	n- butanol (n- Butyl alcohol)					50	152

The following materials had no OELs on our records

- 2, 4, 6-tris[(dimethylamino)methyl]phenol: CAS:90- 72- 2
- benzyl alcohol: CAS:100- 51- 6

PERSONAL PROTECTION

RESPIRATOR

Type AK-P Filter of sufficient capacity

EYE

- Safety glasses with side shields.
- Chemical goggles.

HANDS/FEET

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,.
- When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butatoluene rubber), boots and aprons.
- DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).

OTHER

- Overalls.
- PVC Apron.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear colourless to pale yellow flammable liquid with a solvent odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: Not applicable
Melting Range (°C): Not available
Solubility in water (g/L): Immiscible
pH (1% solution): Not applicable
Volatile Component (%vol): 55- 60
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not available
Autoignition Temp (°C): Not available
State: Liquid

Boiling Range (°C): 100- 143
Specific Gravity (water=1): 0.70- 0.75
pH (as supplied): Not applicable
Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): 24
Upper Explosive Limit (%): Not available
Decomposition Temp (°C): Not Available
Viscosity: Not Available

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 5 of 8

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

HARMFUL- May cause lung damage if swallowed.

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to eyes, respiratory system and skin.

Vapours may cause dizziness or suffocation.

Vapours may cause drowsiness and dizziness.

CHRONIC HEALTH EFFECTS

May cause SENSITISATION by skin contact.

Limited evidence of a carcinogenic effect.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

XYLENE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 4300 mg/kg

Inhalation (human) TCLo: 200 ppm

Inhalation (man) LCLo: 10000 ppm/6h

Inhalation (rat) LC50: 5000 ppm/4h

Oral (Human) LD: 50 mg/kg

Inhalation (Human) TCLo: 200 ppm/4h

Intraperitoneal (Rat) LD50: 2459 mg/kg

Subcutaneous (Rat) LD50: 1700 mg/kg

Oral (Mouse) LD50: 2119 mg/kg

Intraperitoneal (Mouse) LD50: 1548 mg/kg

Intravenous (Rabbit) LD: 129 mg/kg

Inhalation (Guinea) pig: LC 450 ppm/4h

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Reproductive effector in rats

N-BUTANOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 790 mg/kg

Inhalation (human) TCLo: 25 ppm

Inhalation (rat) LC50: 8000 ppm/4h

Dermal (rabbit) LD50: 3400 mg/kg

Inhalation (human) TCLo: 86000 mg/m³

IRRITATION

Skin (rabbit): 405 mg/24h- Moderate

Eye (human): 50 ppm - Irritant

Eye (rabbit): 1.6 mg- SEVERE

Eye (rabbit): 24 mg/24h- SEVERE

2,4,6-TRIS[(DIMETHYLAMINO)METHYL]PHENOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 1200 mg/kg

IRRITATION

Skin (rabbit): 2 mg/24h - SEVERE

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 6 of 8

Section 11 - TOXICOLOGICAL INFORMATION

Oral (rat) LD50: 2500 mg/kg *
Dermal (rabbit) LD50: 1280 mg/kg [Rohm & Haas, Henkel]*

Eye (rabbit): 0.05 mg/24h - SEVERE

Inhalation (rat) LC50: >0.5 mg/l/1 hr.

[Ciba]
The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.
Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

BENZYL ALCOHOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 1230 mg/kg

Inhalation (rat) LCLo: 2000 ppm/4h

Inhalation (rat) LC50: 1000 ppm/8h

Inhalation (rat) LC50: >4178 mg/m³/4h

Dermal (rabbit) LD50: 2000 mg/kg

IRRITATION

Skin (man): 16 mg/48h- Mild

Skin (rabbit): 10 mg/24h open- Mild

Eye (rabbit): 0.75 mg Open SEVERE

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.
(aerosol)

MATERIAL

CARCINOGEN

REPROTOXIN

SENSITISER

SKIN

xylene

IARC:3

ILOEI

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: xylene Category: The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

REPROTOXIN

ILOEI: ILO Chemicals in the electronics industry that have toxic effects on reproduction: xylene

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

Section 13 - DISPOSAL CONSIDERATIONS

• Containers may still present a chemical hazard/ danger when empty.

• Return to supplier for reuse/ recycling if possible.

DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal.

• Recycle wherever possible.

• Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

HAZCHEM: 3[Y]

UNDG:

Dangerous Goods

3

Subrisk:

None

Class:

UN Number:

1263

Packing Group:

III

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or

Air Transport IATA:

ICAO/IATA Class:

3

ICAO/IATA Subrisk:

None

UN/ID Number:

1263

Packing Group:

III

Special provisions:

A3 A72

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 7 of 8

Section 14 - TRANSPORTATION INFORMATION

Cargo Only Packing Instructions:	310	Maximum Qty/Pack:	220 L
Passenger and Cargo Packing Instructions:	309	Passenger and Cargo Maximum Qty/Pack:	60 L
Passenger and Cargo Limited Quantity Packing Instructions:	Y309	Passenger and Cargo Limited Quantity Maximum Qty/Pack:	10 L
Shipping name:PAINT			

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F- E, S- E	Special provisions:	163 223 944 955
Limited Quantities:	5 L		
Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)			

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S5

REGULATIONS

Wattyl Epinamel EH120 Low Temp (LT) Part B (CAS: None):

No regulations applicable

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

- Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)
- Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality
- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia National Pollutant Inventory
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6
- IMO IBC Code Chapter 17: Summary of minimum requirements
- IMO IBC Code Provisional Categorization of Liquid Substances
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- International Agency for Research on Cancer (IARC) Carcinogens
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals
- WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water

n-butanol (CAS: 71-36-3) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- IMO IBC Code Chapter 18: List of products to which the Code does not apply
- IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

2,4,6-tris[(dimethylamino)methyl]pheno (CAS: 90-72-2) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

benzyl alcohol (CAS: 100-51-6) is found on the following regulatory lists;

- Australia Hazardous Substances
- Australia Inventory of Chemical Substances (AICS)
- IMO IBC Code Chapter 17: Summary of minimum requirements
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- International Council of Chemical Associations (ICCA) - High Production Volume List

continued...

WATTYL EPINAMEL EH120 LOW TEMP (LT) PART B

Chemwatch Material Safety Data Sheet

Issue Date: 11-Apr-2008

XC9317EC

CHEMWATCH 5053-48

Version No:8

CD 2007/4 Page 8 of 8

Section 15 - REGULATORY INFORMATION

OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 11-Apr-2008

Print Date: 11-Apr-2008