

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WATTYL POLY U750 MCR PART A

SYNONYMS

"Product Code: 202401, 202403, 202405"

PROPER SHIPPING NAME

PAINT

PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Base or Part A of a 2 pack urethane coating system. Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Apply by brush, hand roller or spray atomisation.

SUPPLIER

Company: Wattyl Pty Ltd

Address:

4 Steel St

Blacktown

NSW, 2148

AUS

Telephone: +61 2 9621 6255

Emergency Tel: 1800 039 008

Fax: +61 2 9831 4244

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

None

RISK

Risk Codes	Risk Phrases
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.
R40(3)	Limited evidence of a carcinogenic effect.
R51	Toxic to aquatic organisms.
R65	HARMFUL- May cause lung damage if swallowed.

SAFETY

Safety Codes	Safety Phrases
S36	Wear suitable protective clothing.
S401	To clean the floor and all objects contaminated by this material use water and detergent.
S13	Keep away from food drink and animal feeding stuffs.
S46	If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	This material and its container must be disposed of as hazardous waste.

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 2 of 8

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
acrylic resin	Various	10-30
xylene	1330-20-7	10-20
aromatic solvent 100	Not avail.	1-9
titanium dioxide	13463-67-7	0-30
filler, unregulated		10-20
n- butyl acetate	123-86-4	1-5
aromatic 150	64742-95-6.	1-5
resin, unregulated		1-5
ingredients not contributing to the classification		1-9
benzene content less than 0.1%		

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.
Treat symptomatically.
for simple esters:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
 - Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- For acute or short term repeated exposures to xylene:
- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
 - Pulmonary absorption is rapid with about 60-65% retained at rest.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.

When any large container (including road and rail tankers) is involved in a fire,

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.

HAZCHEM: 3[Y]

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C).

STORAGE INCOMPATIBILITY

Avoid mixing with alkali metals such as sodium, potassium and lithium.

- **WARNING:** Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively.
- The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.
- Esters react with acids to liberate heat along with alcohols and acids.
- Strong oxidising acids may cause a vigorous reaction with esters that is sufficiently exothermic to ignite the reaction products.
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 4 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	acrylic resin (Inspirable dust (not otherwise classified))		10		
Australia Exposure Standards	xylene (Xylene (o-, m-, p- isomers))	80	350	150	655
Australia Exposure Standards	titanium dioxide (Titanium dioxide (a))		10		
Australia Exposure Standards	n- butyl acetate (n- Butyl acetate)	150	713	200	950

The following materials had no OELs on our records

- aromatic 150:

CAS:64742- 95- 6 CAS:64742- 94- 5

PERSONAL PROTECTION

RESPIRATOR

Type A-P Filter of sufficient capacity

EYE

- Safety glasses with side shields.
- Chemical goggles.

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,

OTHER

- Overalls.
- PVC Apron.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required.

Ventilation equipment should be explosion-resistant.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear or white flammable liquid with a strong sharp solvent odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Sinks in water.

Molecular Weight: Not Available
Melting Range (°C): Not Available
Solubility in water (g/L): Immiscible
pH (1% solution): Not Applicable
Volatile Component (%vol): 30- 35
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not Available
Autoignition Temp (°C): Not Available
State: Liquid

Boiling Range (°C): 127 (IBP)
Specific Gravity (water=1): 1.30- 1.35
pH (as supplied): Not Applicable
Vapour Pressure (kPa): Not Available
Evaporation Rate: Not Available
Flash Point (°C): 23
Upper Explosive Limit (%): Not Available
Decomposition Temp (°C): Not Available
Viscosity: Not Available

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 5 of 8

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

Irritating to skin.

HARMFUL- May cause lung damage if swallowed.

Harmful by inhalation and in contact with skin.

Vapours may cause dizziness or suffocation.

CHRONIC HEALTH EFFECTS

Limited evidence of a carcinogenic effect.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

ACRYLIC RESIN:

No data of toxicological significance identified in literature search.

CAUTION: The chronic health effects of acrylic monomers are under review.

Use good occupational work practices to avoid personal contact.

XYLENE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 4300 mg/kg

Inhalation (human) TCLo: 200 ppm

Inhalation (man) LCLo: 10000 ppm/6h

Inhalation (rat) LC50: 5000 ppm/4h

Oral (Human) LD: 50 mg/kg

Inhalation (Human) TCLo: 200 ppm/4h

Intraperitoneal (Rat) LD50: 2459 mg/kg

Subcutaneous (Rat) LD50: 1700 mg/kg

Oral (Mouse) LD50: 2119 mg/kg

Intraperitoneal (Mouse) LD50: 1548 mg/kg

Intravenous (Rabbit) LD: 129 mg/kg

Inhalation (Guinea) pig: LC 450 ppm/4h

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Reproductive effector in rats

AROMATIC SOLVENT 100:

Not available. Refer to individual constituents.

TITANIUM DIOXIDE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

IRRITATION

Skin (human) 0.3: mg/3d- I Mild

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis.

N-BUTYL ACETATE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 6 of 8

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY

Oral (rat) LD50: 13100 mg/kg
Dermal (rabbit) LD50: 3200 mg/kg*
Inhalation (human) TClO: 200 ppm
Inhalation (rat) LC50: 2000 ppm/4h
Inhalation (Human) TClO: 200 ppm/4h * [PPG]
Oral (Rat) LD50: 10768 mg/kg
Inhalation (Rat) LC50: 390 ppm/4h
Intraperitoneal (Mouse) LD50: 1230 mg/kg
Oral (Rabbit) LD50: 3200 mg/kg
Oral (Guinea) pig: LD50 4700 mg/kg
Intraperitoneal (Guinea) pig: LD 1500 mg/kg

IRRITATION

Skin (rabbit): 500 mg/24h- Moderate
Eye (rabbit): 20 mg (open)- SEVERE
Eye (rabbit): 20 mg/24h - Moderate
Eye (human): 300 mg

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

AROMATIC 150:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 3000 mg/kg
Dermal (rabbit) LD50: >3000 mg/kg
[Manufacturer]

IRRITATION

Nil Reported

MATERIAL

CARCINOGEN

REPROTOXIN

SENSITISER

SKIN

xylene
titanium dioxide

IARC:3
IARC:2B

ILOEI

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: xylene Category: The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

REPROTOXIN

ILOEI: ILO Chemicals in the electronics industry that have toxic effects on reproduction: xylene

CARCINOGEN

IARC: International Agency for Research on Cancer (IARC) Carcinogens: titanium dioxide Category: WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Section 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]

UNDG:

Dangerous Goods
Class:

3

Subrisk:

None

UN Number:

1263

Packing Group:

III

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 7 of 8

Section 14 - TRANSPORTATION INFORMATION

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3 A72		
Cargo Only			
Packing	310	Maximum Qty/Pack:	220 L
Instructions:			
Passenger and Cargo		Passenger and Cargo	
Packing	309	Maximum Qty/Pack:	60 L
Instructions:			
Passenger and Cargo		Passenger and Cargo	
Limited Quantity		Limited Quantity	
Packing	Y309	Maximum Qty/Pack:	10 L
Instructions:			
Shipping name:PAINT			

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F- E, S- E	Special provisions:	163 223 944 955
Limited Quantities:	5 L		
Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)			

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: None

REGULATIONS

Wattyl Poly U750 MCR Part A (CAS: None):
No regulations applicable

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

- Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)
- Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality
- Australia Exposure Standards
- Australia Hazardous Substances
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia National Pollutant Inventory
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6
- IMO IBC Code Chapter 17: Summary of minimum requirements
- IMO IBC Code Provisional Categorization of Liquid Substances
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- International Agency for Research on Cancer (IARC) Carcinogens
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals
- WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water

titanium dioxide (CAS: 13463-67-7) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines
- Australia Therapeutic Goods Administration (TGA) Sunscreening agents permitted as active ingredients in listed products
- CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP
- IMO IBC Code Chapter 17: Summary of minimum requirements
- International Agency for Research on Cancer (IARC) Carcinogens
- OECD Representative List of High Production Volume (HPV) Chemicals

titanium dioxide (CAS: 1317-70-0) is found on the following regulatory lists;

- Australia Inventory of Chemical Substances (AICS)
- OECD Representative List of High Production Volume (HPV) Chemicals

titanium dioxide (CAS: 1317-80-2) is found on the following regulatory lists;

- Australia Inventory of Chemical Substances (AICS)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
- OECD Representative List of High Production Volume (HPV) Chemicals

n-butyl acetate (CAS: 123-86-4) is found on the following regulatory lists;

continued...

WATTYL POLY U750 MCR PART A

Chemwatch Material Safety Data Sheet

Issue Date: 18-Mar-2008

XC9317EC

CHEMWATCH 5127-94

Version No:5

CD 2007/4 Page 8 of 8

Section 15 - REGULATORY INFORMATION

Australia Exposure Standards
Australia Hazardous Substances
Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
IMO IBC Code Chapter 17: Summary of minimum requirements
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals
United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II

aromatic 150 (CAS: 64742-95-6) is found on the following regulatory lists;

Australia Hazardous Substances
Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

aromatic 150 (CAS: 64742-94-5) is found on the following regulatory lists;

Australia Hazardous Substances
Australia High Volume Industrial Chemical List (HVICL)
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for acrylic resin as CAS: Various.

No data available for aromatic solvent 100 as CAS: Not avail.

No data available for titanium dioxide as CAS: 12188-41-9.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
titanium dioxide	13463- 67- 7, 1317- 70- 0, 1317- 80- 2, 12188- 41- 9
aromatic 150	64742- 95- 6, 64742- 94- 5

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 18-Mar-2008

Print Date: 18-Mar-2008