

WATTYL L760 THINNER

Chemwatch Material Safety Data Sheet

Issue Date: 12-Feb-2008

XC9317EC

CHEMWATCH 02-1000

Version No:1

CD 2007/4 Page 1 of 6

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WATTYL L760 THINNER

SYNONYMS

"Product Code: 200010", "enamel thinner solvent thinning liquid"

PROPER SHIPPING NAME

PAINT RELATED MATERIAL

PRODUCT USE

Used as thinner to reduce viscosity of enamels prior to application by spray atomisation. May also be used to clean equipment.

SUPPLIER

Company: Watty! Pty Ltd

Address:

4 Steel St

Blacktown

NSW, 2148

AUS

Telephone: +61 2 9621 6255

Emergency Tel: 1800 039 008

Fax: +61 2 9831 4244

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

POISONS SCHEDULE

S6

RISK

Risk Codes	Risk Phrases
R10	Flammable.
R20/21/22	Harmful by inhalation in contact with skin and if swallowed.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R52	Harmful to aquatic organisms.
R65	HARMFUL- May cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes	Safety Phrases
S36	Wear suitable protective clothing.
S401	To clean the floor and all objects contaminated by this material use water and detergent.
S13	Keep away from food drink and animal feeding stuffs.
S46	If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
xylene	1330-20-7	>60
n- butanol	71-36-3	10-30

Solvent grades have less than 0.1% benzene content

continued...

WATTYL L760 THINNER

Chemwatch Material Safety Data Sheet

Issue Date: 12-Feb-2008

XC9317EC

CHEMWATCH 02-1000

Version No:1

CD 2007/4 Page 2 of 6

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

To treat poisoning by the higher aliphatic alcohols:

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.

For acute or short term repeated exposures to xylene:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- Pulmonary absorption is rapid with about 60-65% retained at rest.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
 - Moderate fire hazard when exposed to heat or flame.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.

HAZCHEM: 3[Y]

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.

continued...

WATTYL L760 THINNER

Chemwatch Material Safety Data Sheet
Issue Date: 12-Feb-2008
XC9317EC

CHEMWATCH 02-1000
Version No:1
CD 2007/4 Page 3 of 6

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C).

STORAGE INCOMPATIBILITY

Avoid storage with strong acids, acid chlorides, acid anhydrides, oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³
Australia Exposure Standards	xylene (Xylene (o-, m-, p- isomers))	80	350	150	655		
Australia Exposure Standards	n- butanol (n- Butyl alcohol)					50	152

PERSONAL PROTECTION

RESPIRATOR

Type A Filter of sufficient capacity

EYE

- Safety glasses with side shields.
- Chemical goggles.

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,

OTHER

- Overalls.
- PVC Apron.

ENGINEERING CONTROLS

CARE: Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear.

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

continued...

WATTYL L760 THINNER

Chemwatch Material Safety Data Sheet

Issue Date: 12-Feb-2008

XC9317EC

CHEMWATCH 02-1000

Version No:1

CD 2007/4 Page 4 of 6

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless flammable liquid with a strong solvent odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: Not available
Melting Range (°C): Not available.
Solubility in water (g/L): Immiscible
pH (1% solution): Not available.
Volatile Component (%vol): 100
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): 1.0
Autoignition Temp (°C): 426
State: Liquid

Boiling Range (°C): 108- 145
Specific Gravity (water=1): 0.84
pH (as supplied): Not applicable
Vapour Pressure (kPa): >1
Evaporation Rate: Not available
Flash Point (°C): 25 (OC- lit)
Upper Explosive Limit (%): 10.9
Decomposition Temp (°C): Not Available
Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

HARMFUL- May cause lung damage if swallowed.

Risk of serious damage to eyes.

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to respiratory system and skin.

Vapours may cause dizziness or suffocation.

Vapours may cause drowsiness and dizziness.

CHRONIC HEALTH EFFECTS

Not applicable.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

XYLENE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 4300 mg/kg

Inhalation (human) TLo: 200 ppm

Inhalation (man) LLo: 10000 ppm/6h

Inhalation (rat) LC50: 5000 ppm/4h

Oral (Human) LD: 50 mg/kg

Inhalation (Human) TLo: 200 ppm/4h

Intraperitoneal (Rat) LD50: 2459 mg/kg

Subcutaneous (Rat) LD50: 1700 mg/kg

Oral (Mouse) LD50: 2119 mg/kg

Intraperitoneal (Mouse) LD50: 1548 mg/kg

Intravenous (Rabbit) LD: 129 mg/kg

Inhalation (Guinea) pig: LC 450 ppm/4h

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

The substance is classified by IARC as Group 3:

IRRITATION

Skin (rabbit):500 mg/24h Moderate

Eye (human): 200 ppm Irritant

Eye (rabbit): 87 mg Mild

Eye (rabbit): 5 mg/24h SEVERE

continued...

WATTYL L760 THINNER

Chemwatch Material Safety Data Sheet

Issue Date: 12-Feb-2008

XC9317EC

CHEMWATCH 02-1000

Version No:1

CD 2007/4 Page 5 of 6

Section 11 - TOXICOLOGICAL INFORMATION

NOT classifiable as to its carcinogenicity to humans.
Evidence of carcinogenicity may be inadequate or limited in animal testing.
Reproductive effector in rats

N-BUTANOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 790 mg/kg

Inhalation (human) TClO: 25 ppm

Inhalation (rat) LC50: 8000 ppm/4h

Dermal (rabbit) LD50: 3400 mg/kg

Inhalation (human) TClO: 86000 mg/m³

IRRITATION

Skin (rabbit): 405 mg/24h- Moderate

Eye (human): 50 ppm - Irritant

Eye (rabbit): 1.6 mg- SEVERE

Eye (rabbit): 24 mg/24h- SEVERE

MATERIAL	CARCINOGEN	REPROTOXIN	SENSITISER	SKIN
xylene		ILOEI		

REPROTOXIN

ILOEI: ILO Chemicals in the electronics industry that have toxic effects on reproduction: xylene

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms.

This material and its container must be disposed of as hazardous waste.

Section 13 - DISPOSAL CONSIDERATIONS

· Containers may still present a chemical hazard/ danger when empty.

· Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

DO NOT allow wash water from cleaning or process equipment to enter drains.

It may be necessary to collect all wash water for treatment before disposal.

· Recycle wherever possible.

· Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

HAZCHEM: 3[Y]

UNDG:

Dangerous Goods Class: 3 Subrisk: None

UN Number: 1263 Packing Group: III

Shipping Name: PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Air Transport IATA:

ICAO/IATA Class: 3 ICAO/IATA Subrisk: None

UN/ID Number: 1263 Packing Group: III

Special provisions: A3 A72

Shipping name: PAINT RELATED MATERIAL

Maritime Transport IMDG:

IMDG Class: 3 IMDG Subrisk: None

UN Number: 1263 Packing Group: III

EMS Number: F- E, S- E Special provisions: 163 223 944 955

Limited Quantities: 5 L

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

continued...

WATTYL L760 THINNER

Chemwatch Material Safety Data Sheet

Issue Date: 12-Feb-2008

XC9317EC

CHEMWATCH 02-1000

Version No:1

CD 2007/4 Page 6 of 6

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE: S6

REGULATIONS

Wattyl L760 Thinner (CAS: None):

No regulations applicable

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

- Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)
- Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality
- Australia Dangerous Goods Code (ADG Code) - Goods Too Dangerous To Be Transported
- Australia Dangerous Goods Code Draft 7th Edition - Goods too Dangerous to be Transported
- Australia Exposure Standards
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)
- Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water

n-butanol (CAS: 71-36-3) is found on the following regulatory lists;

- Australia Exposure Standards
- Australia High Volume Industrial Chemical List (HVICL)
- Australia Inventory of Chemical Substances (AICS)
- IMO IBC Code Chapter 18: List of products to which the Code does not apply
- IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
- International Council of Chemical Associations (ICCA) - High Production Volume List
- OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 12-Feb-2008

Print Date: 12-Feb-2008