



SURFACE PREPARATION Timber

I-14

PURPOSE

This section provides general information on the surface preparation of old/previously coated and new timber. Removal of oils, and filling imperfections.

INTRODUCTION

Timber is used extensively in the boat building industry - typically masts, tillers, oars and planked hulls. A well-maintained timber boat can last for a long time. In all cases, correct surface preparation is essential for optimum performance.

New Timber

Depending on the type of timber used by manufacturers, oils from the timber may need to be removed prior to any other surface preparation. These contaminants are detrimental to the adhesion of a coating system.

Old/Previously Coated Timber

The removal of all oil, grease, fat and other contaminants is essential prior to any other surface preparation. In most cases, the existing coating system will need to be removed entirely to ensure a sound base for the new system.



SURFACE PREPARATION Timber

I-14

SURFACE PREPARATION

In order to ensure good adhesion and long term performance of any coating for timber, it is essential that the correct type of surface preparation is carried out. The removal of chemicals, oil, grease and fat must be completed before any other preparation work commences.

Removal of Oils

For oily timbers such as teak the timber surface should be:

- Scrubbed with Thinner L703 to remove all traces of oil.
- Dry sand to a clean, smooth surface.
- Dry before painting.
- Ensure all sanding dust is removed.

Filling Imperfections

Imperfections should be addressed using the following method:

- Abrade the surface thoroughly to a clean, smooth surface.
- Remove all sanding dust.
- Remove all oils by scrubbing with Thinner L703 if necessary.
- Prime the surface using Seapro TP80 (timber preserver) and allow to cure - refer to relevant data sheet.
- Fill the primed imperfection with Seapro EFC (epoxy fairing compound).
- Sand the Seapro EFC (epoxy fairing compound) to give a smooth, even finish.
- Overcoat with Epinamel UC230 (undercoat).

CUSTOMER SERVICE HOTLINE 132101 (Aust), 0800 735 551 (NZ)

Wattyl® is a registered trademark of Wattyl Australia Pty Ltd.

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive. 3. For all product and non-product related information, Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office. 4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.
WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)